

**WORKMATE™**  
**ELECTRIC CHAIN HOISTS**

**SPANCO®**  
Promise to Perform Industries, Inc.

**THE PERFECT PARTNER FOR YOUR CRANE**



**WARNING**  
Failure to follow these warnings may result in death, severe injury, or property damage.

- Do not operate this hoist with a damaged load chain or malfunctioning hoist.
- Do not lift loads or hoist over people.
- Do not lift more than rated load.
- Do not use hoist unless tested to meet ASME B30.26.
- Do not operate with broken, twisted, or damaged hoist or load chain.
- Do not operate a hoist with a malfunctioning hoist or load chain.
- Do not remove or obscure warning labels.

Spanco®  
Spanco Industries, Inc. 10000 S. 10th St. Suite 100  
Tulsa, OK 74116  
1-800-333-3333  
www.spanco.com

# WORKMATE™ ELECTRIC CHAIN HOISTS

Quality and reliability are at the heart of our Workmate™ Electric Chain Hoists. The Workmate is built with a modern design that allows for a lightweight frame and sacrifices no capacity to do so. The ability to handle industrial grade applications alongside the Workmate's durable components make it a superior product to other chain hoists in its weight class.



Jib Crane

## FEATURED OFFERING:

- Electric Chain Hoists can be paired with Spanco Gantry, Workstation, and Jib Cranes
- Available with capacities of 1/4-Ton, 1/2-Ton, 1-Ton and 2-Ton
- Lift heights from 10' - 20' in one-foot increments
- Available voltages are 110V, 230V, and 460V
- 42V controls




Gantry Crane



Freestanding Workstation

Base Model	Capacity (Tons)	Phase	Voltage	Speed	Speed (ft/min) 60Hz	Duty Rating HMI	Falls
<b>SINGLE PHASE OFFERING</b>							
SP250	1/4-Ton	Single	110V/60Hz 230V/60Hz	Single	16 FPM	H4	1
SP500	1/2-Ton	Single	110V/60Hz 230V/60Hz	Single	16 FPM	H4	1
	1-Ton	Single	110V/60Hz 230V/60Hz	Single	8 FPM	H4	2
SP1000	1-Ton	Single	110V/60Hz 230V/60Hz	Single	4.8 FPM	H4	1
<b>3-PHASE OFFERING</b>							
SP250	1/4-Ton	Three	230V/60Hz 460V/60Hz	Dual	32/8 FPM	H4	1
SP500	1/2-Ton	Three	230V/60Hz 460V/60Hz	Dual	32/8 FPM	H4	1
	1-Ton	Three	230V/60Hz 460V/60Hz	Dual	16/4 FPM	H4	2
SP1000	1-Ton	Three	230V/60Hz 460V/60Hz	Dual	32/8 FPM	H4	1
	2-Ton	Three	230V/60Hz 460V/60Hz	Dual	16/4 FPM	H4	2
SP2000	2-Ton	Three	230V/60Hz 460V/60Hz	Dual	32/8 FPM	H4	1

## PRODUCT FEATURES:



### MOTOR

Duty cycle rating of H4. External motor with cooling fins and fan wheel has 30% reduction in operating temperature (140°F)

Keyless shaft-to-pocket wheel connection, built to a self-centering polygonal design. Faster to reassemble, less strain on shaft



### INDUSTRY IP65 PROTECTION

built for all environments. The hoist bodies are dust tight, water jet resistant, and have built in housing drains, while the chains have a corrosion resistant coating.



### DC-SPRING-LOADED BRAKE

Requires rectifier AC to DC  
 Brake release when energized  
 Maintenance-free and highly reliable  
 Single-disc brake with two friction surfaces



### CLOSED GEARBOX

Modular, self-enclosed and permanently lubricated gearbox eliminates mess during disassembly



### EYEBOLT SUSPENSION

Made of aluminum die cast  
 Hinged by loosening one screw making it easier to install.




### CHAIN

The case hardened and manganese phosphate profile steel chain provides about 15% more capacity at an identical nominal diameter when compared to the traditional round steel chain

With 15% increased lifting capacity at the same chain diameter, the chain is 20-60% lighter than major competitors in its class

The larger cross-sectional area reduces wear and increases the lifetime of the chain. The load hook with stable, guided hook latch and safety rubber buffer provides maximum safety



Salt Spray Test before and after:



## INDUSTRIES SERVED



**MATERIAL  
HANDLING**



**AUTOMOTIVE**



**RIGGING**



**METAL  
FABRICATION**



**MUNICIPAL  
MAINTENANCE**



**CONSTRUCTION**

## SPANCO WARRANTY

### Two-Year Warranty Coverage:

- Defects in equipment material and workmanship of Spanco Workmate electric chain hoists and equipment
- Defects in equipment material and workmanship of motorized systems and equipment
- Paint coatings and finishes in normal operating environments
- Excludes wear items

Spanco warrants motorized equipment to be free from defects in material and workmanship for a period of two (2) years, commencing on the date of shipment to the first retail purchaser. Spanco warrants its paint and finishes for a period of two (2) years. Warranty claims related to coatings must be accompanied by documentation of the product's application and environmental conditions from time of delivery to time of claim.

### Warranty Terms & Conditions:

Spanco terms and conditions can be found on the website at [www.spanco.com](http://www.spanco.com).



Promise to Perform Industries, Inc. ■ Morgantown, PA ■ Las Vegas, NV  
■ [Spanco.com](http://Spanco.com) Toll Free: 800-869-2080 ■ Mexico: 1-610-286-7200



©2023 Promise to Perform Industries Inc. All rights reserved. All specifications and product designs subject to change without notice. All trademarks are the sole property of their respective owners. SP-WMH-BR0523